

EASY TO INSTALL

The **STS400™** saves manufacturers in installation costs and time – 100% pre-assembled and calibrated – with no focusing, no height barrier and no encoder requirement. The high read rates are guaranteed by the factory-validated reading performance. Additionally, the self-contained mechanical layout makes the integration into constrained spaces quick and easy. The complete reading system fits into a maximum space of:

1080 x 241 x 176 mm - 42.5 X 9.6 x 7 in (cables, connection boxes, and readers included).

EASY TO MAINTAIN

With no moving parts, the **STS400™** requires minimal maintenance. Detecting a reading problem is simple with the Green Spot feature: a flashing green light indicates a good read at the single device level, providing immediate feedback of the read status without any additional software tools or displays.

SIMPLE AND COMPACT

The imaging approach provides a simple reader layout. This approach eliminates the need for complex articulated mounting patterns, typical of other reading technologies. Easy integration and compactness of the reading system are exclusive advantages of the imaging approach.

LONG-TERM RELIABILITY

No moving parts guarantee reliability and a longer life-cycle. Imagers offer values of MTBF (Mean Time Between Failures) several times longer than readers working with moving parts, such as rotating mirrors in laser scanners.

READY FOR THE FUTURE

Driven by physical constraints, upgrades of the tire labeling, or government mandates, manufacturers have to comply with the downsizing of the bar code heights or the introduction of 2D bar codes. 2D imagers are the ideal solution for these changing requirements. The downsizing of bar code height and reading 2D bar codes can present challenges for other reading technologies. Solutions based on 2D imagers are a reliable investment, ensuring high read rates, durable life-cycle and adaptability to future requirements.



MATRIX410™

The **MATRIX 410™ ATS** offers a single, self-contained reading head, including illuminator and lens. It is pre-mounted with the best optical setup and parameter configuration, ready to read in-line when powered on.

The **MATRIX 410™** also features the extra power illuminator (**MATRIX 410™ ATS-100**) which provides the optimal solution for single head reading stations used in many tire manufacturing stages such as Visual Inspection, Trimming or Testing.



HEADQUARTERS

Datalogic Automation Srl

Via Lavino, 265
40050 Monte San Pietro - Bologna - Italy
Tel: +39 051/6765611
info.automation.it@datalogic.com

BRANCHES AND SALES OFFICES

EUROPE BENELUX

Datalogic Automation Benelux

Newtonweg 3
4104 BK Culemborg - The Netherlands
Tel. +31 345/589489
info.automation.nl@datalogic.com

FRANCE

Datalogic Automation Srl

Succursale en France
Le Parc Technologique de Lyon
333 cours du 3ème Millénaire - Le Pôle
69800 Saint Priest
Tél. +33 (0)4/72476180
info.automation.fr@datalogic.com

GERMANY

Datalogic Automation Srl

Niederlassung Central Europe
Gottlieb-Stoll-Straße 1,
73271 Holzmaden
Tel. +49 7023 7453-100
info.automation.de@datalogic.com

ITALY

Datalogic Automation Italy

Via Lavino, 265
40050 Monte San Pietro - Bologna
Tel. +39 051/6765611
info.automation.it@datalogic.com

Via Taormina 1
20093 - Cologno Monzese (MI) Italy
Tel. +39 02 25151211
info.automation.it@datalogic.com

Via Le Gorrey, 10 11020, Donnas - Aosta
Tel. +39-0125-8128201
info.automation.it@datalogic.com

SPAIN

Datalogic Automation Iberia

Sucursal en España
C/ Frederic Mompou 4 esc A, 4ª puerta 3ª
08960 Sant Just Desvern - Barcelona
Tel. +34 (0)93/4772059

NORDIC

Datalogic Automation AB

Höjdrodergatan 21
21239 Malmö - Sweden
Tel. +46 (0)40/385000
info.automation.se@datalogic.com

UNITED KINGDOM

Datalogic Automation UK

Datalogic House
Dunstable Road, Redbourn - Hertfordshire
AL3 7PR
Tel. +44 (0) 1582 791750
info.automation.uk@datalogic.com

TURKEY

Datalogic ADC Turkey

Merkezi İtalya İstanbul Merkez Şubesi Süleyman
Seba Cad. No:48 BJK Plaza A. Blok Kat:4 D.44
34357 - İstanbul - Turkey
Tel. +90 212 396 1550
info.adc.tr@datalogic.com

NORTH AMERICA

Datalogic Automation Inc

511 School House Road
Telford, PA 18969-1196 - United States
Tel. +1-800-BAR-CODE or +1-215-723-0981
info.automation.us@datalogic.com

Datalogic Automation Inc

MACHINE VISION
5775 W Old Shakopee Rd
STE 160, Bloomington, MN 55437
United States
Tel. +1-952-996-9500
info.automation.us@datalogic.com

SOUTH AMERICA

Datalogic Brazil

Avenida Olivio Roncoletta, 465
Bairro Vila Hortolandia Jundiá (SP), Brazil
Tel. +55 11 29232600
info.automation.br@datalogic.com

APAC

Australia-New Zealand

Datalogic Automation Pty Ltd

Unit 130, 45 Gilby Road
Mt Waverley - Victoria, 3149 - Australia
Tel. +61 (0)3/95589299
info.automation.au@datalogic.com

CHINA

Datalogic Automation Asia

2nd Floor, 10 Building, Dayuan Industrial Zone,
No.1, Pingshan 1st Road,
Liuxuan Blvd. Xili, Nanshan District,
518054, Shenzhen, China
Tel: +86 (0)755-8629 6779
info.automation.cn@datalogic.com

Suite 1301, Hua Rong Plaza,
1289 South Pudong Road, Pudong District
Shanghai 200120
Tel: +86 (0)21-5836 6692
info.automation.cn@datalogic.com

Floor 20, Room 2019, Building 2,
16 West Nan San Huan Road
Fengtai District, Beijing
Tel: +86 (0)10-8757 6375
info.automation.cn@datalogic.com

1202, Excellence Build, 128 Yanji Road,
Shibe District, Qingdao, China
Tel: +86 (0)532 55787889

JAPAN

Idec Auto-Id Solutions Corporation

8-10, Shioe 5-chome, Amagasaki Hyogo,
Japan 661-0976
Tel. +81-6-7711-8880
www.idec.com

Rev. 06_01/2015



9C511900E


Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.



DATALOGIC
THE VISION IS YOURS

www.datalogic.com

< STS400™ >



Solutions for Tire Sorting

STS400™ SOLUTIONS FOR TIRE SORTING

The **STS400™** is the first solution in its class to effectively address the demanding requirements of tire Tracking and Traceability applications.


Tracking and Traceability are critical aspects in tire manufacturing. In logistics, WIP, quality control, and compliance, tires are tracked during every step of the production process. From raw materials through tire assembly to the end-of-line sorting, the ability to read bar codes on tires is a necessary, but difficult, task. It calls for omni-directional reading of low aspect ratio bar codes, whose quality degenerates during the manufacturing process. If the correct technology is not applied, it may result in loss of production efficiency, additional manual handling, and extra costs for compliance management.

The **STS400™** is extremely compact and mounted on a self-contained structure. This solution delivers the highest reading performance with simple, user-friendly installation and maintenance. The solution is pre-assembled and calibrated, making integration into a tire sorting system the fastest in the industry. In less than one hour, with no special tools or training, the **STS400™** can go from the shipping carton to reading tires on the production line!



PERFORMANCE


The **MATRIX 410™** is the ideal solution for high speed sortation with minimal distance between tires.



The **MATRIX 410™** can read hard to read bar codes and transfer large images over the Ethernet, with a full bitmap resolution.

Since the entire bar code is caught in a single capture, the **MATRIX 410™** guarantees the best performance for image acquisition and performs advanced processing algorithms for bar code location and decoding. These features are extremely critical when reading low aspect ratio bar codes, especially when they are dirty or damaged.

Powerful illuminators have been specifically designed for tire applications to increase the depth-of-field and improve the reliability of reading, even when faced with damaged or low contrast bar codes.



ONE SOLUTION-ONE PART NUMBER

Each complete **STS400™** solution has a single order number. All of the required accessories, such as cables, connectors and photocells, are included into the shipping package. Only the power supply is ordered separately.

MODELS

STS400™ models are optimized for bar code resolution and reading range: models are configured to read 0.25 mm (10 mil) and 0.33 mm (13 mil) for passenger, light truck tires and 0.35 mm (14 mil) for commercial vehicle tires.

STS400 - STANDARD READING RANGE

STS400™ is available in different versions - fully pre-configured and optimized - for any possible reading layout:


- top reading (versions -00x and 01x)
- bottom reading (versions -02x)
- side reading (versions -03x)



STS400 - LONG READING RANGE

The **STS400™** long reading range is the perfect identification solution for industrial vehicle tire sorting applications, offering a simple solution that meets the demanding requirements of reading large tires.

With its ultra-powerful, integrated illuminator, the **STS400™** long reading range delivers unprecedented reading coverage setting a new standard for automatic identification in the tire industry.





STS400™ - SOLUTIONS FOR TIRE SORTING

MODEL SELECTION

Finding the right solution for any application is easy. The only information required is the bar code resolution and the conveyor width to identify a single order number for a complete reading solution.

A simple match table is available for a quick model selection.



Part	Description	Position	Reading Width	OD	Min. Reading Dist	Max. Reading Dist
STS400™						
337401023	STS400-001 SOKUT TIRE SORT 3 HEAD ST RES	8.30 (32)	545 (21.2)	250 (9.8)	890 (35.0)	1140 (44.9)
337401024	STS400-006 SOKUT TIRE SORT 6 HEAD ST RES	8.30 (32)	545 (21.2)	250 (9.8)	890 (35.0)	1140 (44.9)
337401025	STS400-007 SOKUT TIRE SORT 7 HEAD ST RES	8.30 (32)	545 (21.2)	250 (9.8)	890 (35.0)	1140 (44.9)
337401026	STS400-008 SOKUT TIRE SORT 8 HEAD ST RES	8.30 (32)	545 (21.2)	250 (9.8)	890 (35.0)	1140 (44.9)
337401027	STS400-010 SOKUT TIRE SORT 5 HEAD H8 RES	8.25 (32)	633 (25.0)	200 (7.9)	710 (28.0)	910 (35.8)
337401028	STS400-016 SOKUT TIRE SORT 6 HEAD H8 RES	8.25 (32)	743 (29.3)	200 (7.9)	710 (28.0)	910 (35.8)
337401029	STS400-017 SOKUT TIRE SORT 7 HEAD H8 RES	8.25 (32)	853 (33.5)	200 (7.9)	710 (28.0)	910 (35.8)
337401030	STS400-018 SOKUT TIRE SORT 8 HEAD H8 RES	8.25 (32)	963 (38.0)	200 (7.9)	710 (28.0)	910 (35.8)
MATRIX 410 Assembly for Tire Solutions						
337401035	Matrix 410 ATS-001 ASSEMBLY FOR STS400-00X	8.30 (32)	340 (13.4)	250 (9.8)	890 (35.0)	1140 (44.9)
337401036	Matrix 410 ATS-010 ASSEMBLY FOR STS400-01X	8.25 (32)	195 (7.7)	200 (7.9)	710 (28.0)	910 (35.8)

STS400 - TOP READING PASSENGER LIGHT TRUCKS

PN	DESCRIPTION	READERS	1D CODE RES MM (MILS)	READING WIDTH MM (INCH)	MIN READING DIST MM (INCH)	MAX READING DIST MM (INCH)	DOF MM (INCH)	FOCAL POSITION MM (INCH)
937401023	STS400-005 SOLUT TIRE SORT 5_HEAD ST RES	5	0,30 (11,8)	805 (31,7)	890 (35,0)	1140 (44,9)	250 (9,8)	1065 (41,9)
937401024	STS400-006 SOLUT TIRE SORT 6_HEAD ST RES	6	0,30 (11,8)	945 (37,2)	890 (35,0)	1140 (44,9)	250 (9,8)	1065 (41,9)
937401025	STS400-007 SOLUT TIRE SORT 7_HEAD ST RES	7	0,30 (11,8)	1085 (42,7)	890 (35,0)	1140 (44,9)	250 (9,8)	1065 (41,9)
937401026	STS400-008 SOLUT TIRE SORT 8_HEAD ST RES	8	0,30 (11,8)	1225 (48,2)	890 (35,0)	1140 (44,9)	250 (9,8)	1065 (41,9)
937401027	STS400-015 SOLUT TIRE SORT 5_HEAD HI RES	5	0,25 (9,8)	635 (25,0)	710 (28,0)	910 (35,8)	200 (7,9)	788 (31,0)
937401028	STS400-016 SOLUT TIRE SORT 6_HEAD HI RES	6	0,25 (9,8)	745 (29,3)	710 (28,0)	910 (35,8)	200 (7,9)	788 (31,0)
937401029	STS400-017 SOLUT TIRE SORT 7_HEAD HI RES	7	0,25 (9,8)	855 (33,7)	710 (28,0)	910 (35,8)	200 (7,9)	788 (31,0)
937401030	STS400-018 SOLUT TIRE SORT 8_HEAD HI RES	8	0,25 (9,8)	965 (38,0)	710 (28,0)	910 (35,8)	200 (7,9)	788 (31,0)

STS400 - BOTTOM AND HOOK CHAIN READING PASSENGER LIGHT TRUCKS


PN	DESCRIPTION	READERS	1D CODE RES MM (MILS)	READING WIDTH MM (INCH)	MIN READING DIST MM (INCH)	MAX READING DIST MM (INCH)	DOF MM (INCH)	FOCAL POSITION MM (INCH)
937400018	STS400-205 SOL TIRE BOTTOM 5_HD ST RES	5	0,30 (11,8)	754 (29,7)	317 (12,5)	457 (18,0)	140 (5,5)	380 (15,0)
937400019	STS400-206 SOL TIRE BOTTOM 6_HD ST RES	6	0,30 (11,8)	894 (35,2)	317 (12,5)	457 (18,0)	140 (5,5)	380 (15,0)
937400020	STS400-305 SOL TIRE HOOK CH. 5_HD ST RES	5	0,30 (11,8)	748 (29,4)	405 (15,9)	560 (22,0)	155 (6,1)	483 (19,0)
937400021	STS400-306 SOL TIRE HOOK CH. 6_HD ST RES	6	0,30 (11,8)	888 (35,0)	405 (15,9)	560 (22,0)	155 (6,1)	483 (19,0)

STS400 - LONG RANGE COMMERCIAL VEHICLE TIRES

PN	DESCRIPTION	READERS	1D CODE RES MM (MILS)	READING WIDTH MM (INCH)	MIN READING DIST MM (INCH)	MAX READING DIST MM (INCH)	DOF MM (INCH)	FOCAL POSITION MM (INCH)
937401037	STS400-105 SOLUT TIRE 5_HEAD LONG RANGE	5	0,35 (13,8)	805 (31,7)	880 (34,6)	1280 (50,4)	400 (15,7)	1065 (41,9)
937401038	STS400-106 SOLUT TIRE 6_HEAD LONG RANGE	6	0,35 (13,8)	945 (37,2)	880 (34,6)	1280 (50,4)	400 (15,7)	1065 (41,9)
937401039	STS400-107 SOLUT TIRE 7_HEAD LONG RANGE	7	0,35 (13,8)	1085 (42,7)	880 (34,6)	1280 (50,4)	400 (15,7)	1065 (41,9)
937401040	STS400-108 SOLUT TIRE 8_HEAD LONG RANGE	8	0,35 (13,8)	1225 (48,2)	880 (34,6)	1280 (50,4)	400 (15,7)	1065 (41,9)
937401085	STS400-115 SOLUT TIRE 5_HEAD HI RES LR	5	0,25 (10)	625 mm	930 mm	1310 mm	380 mm	1080 mm
937401086	STS400-116 SOLUT TIRE 6_HEAD HI RES LR	6	0,25 (10)	735 mm	930 mm	1310 mm	380 mm	1080 mm
937401087	STS400-117 SOLUT TIRE 7_HEAD HI RES LR	7	0,25 (10)	845 mm	930 mm	1310 mm	380 mm	1080 mm
937401088	STS400-118 SOLUT TIRE 8_HEAD HI RES LR	8	0,25 (10)	955 mm	930 mm	1310 mm	380 mm	1080 mm

MATRIX 410 - ATS ASSEMBLIES FOR TIRES SOLUTIONS

PN	DESCRIPTION	1D CODE RES MM (MILS)	READING WIDTH MM (INCH)	MIN READING DISTMM (INCH)	MAX READING DIST MM (INCH)	DOF MM (INCH)	FOCAL POSITION MM (INCH)
937401035	MATRIX 410 ATS-000 ASSY FOR STS400-00X	0,30 (11,8)	245 (9,6)	890 (35,0)	1140 (44,9)	250 (9,8)	1065 (41,9)
937401036	MATRIX 410 ATS-010 ASSY FOR STS400-01X	0,25 (9,8)	195 (7,7)	710 (28,0)	910 (35,8)	200 (7,9)	788 (31,0)
937400022	MATRIX 410 ATS-200 ASSY FOR STS400-20X	0,30 (11,8)	194 (7,6)	317 (12,5)	457 (18,0)	140 (5,5)	380 (15,0)
937400023	MATRIX 410 ATS-300 ASSY FOR STS400-30X	0,30 (11,8)	188 (7,4)	405 (15,9)	560 (22,0)	155 (6,1)	483 (19,0)
937401041	MATRIX 410 ATS-100 ASSY FOR STS400-10X	0,35 (13,8)	245 (9,6)	880 (34,6)	1280 (50,4)	400 (15,7)	1065 (41,9)



WEBSENTINEL-IMAGES™

DESCRIPTION

Datalogic WebSentinel™-IMAGES is the remote management software solution for monitoring the operational activities of reading devices. This platform collects and archives all the critical information related to functional status, including diagnostics, performance and working images.

Captured images provide an effective and precise analysis of processes and reading performance. Because of the high level of data integrity and intrinsic vividness, captured images are an excellent forensic tool. Analysis of unsuccessful reading attempts provides quick and precise problem diagnosis, resulting in superior reading performance.

WebSentinel™ integrates a user-friendly, web-based interface for remote data representation and control. While the central application runs on a server machine, users can access data and control the operational functionalities through a standard web browser, such as Internet Explorer or Google Chrome. No additional software components are required.

Captured images are automatically transferred from the readers to the WebSentinel-IMAGES™ database for archiving. Images are linked to the information of the specific object scanned. For example: basic no-read information, such as timestamp of the event can be correlated [or linked] to the set of working images captured during the reading attempt.

An advanced research tool allows users to quickly locate events of interest and access an image preview, resulting in a fast evaluation of the entire reading phase.



Event ID	Timestamp	Device ID	Status	Category	Resolution
51	7/22/11 11:26:50	0003654661	Good read	C	True
53	7/22/11 11:26:50	01000458	Good read	G	True
55	7/22/11 11:39:59	0003654661	Good read	C	True

The screenshot shows a web-based interface with a table of event data and a grid of image thumbnails below it. The table has columns for event ID, timestamp, device ID, status, category, and resolution. The grid contains multiple rows of small images, with some images highlighted in green, indicating successful reads or specific events of interest.

